Product Specification/Data Sheet



PRODUCT DETAILS:

Product Name:	Eden
Product Type:	Fabric tile
Product Shape:	Quad, hexagon, fan, rhombus, circle, doughnut, cloud.
Product Code:	ED(W/C)/XX.XX.XX

PRODUCT IMAGE:



SPECIFICATION:

Consists of either a 40mm or 64mm thick fabric tile.

Tile width available between 200mm and 1600mm. Tile depth available between 200mm and 1600mm.

Tile construction is from 12mm medium density fibreboard (MDF) adhered (using water based adhesive) to either 25mm or 50mm sound absorbing foam.

12mm medium density fibreboard (MDF) is Forest Stewardship Council® (FSC®) certified (FSC-C200033).

Sound absorbing foam is tested to BSEN ISO 354 and has a noise reduction co-efficient (NRC) of 0.55 for 25mm thick and 0.90 for 50mm thick. Technical report ref no: C/23213/T01.

Tile is upholstered (using water based adhesive) in 1mm thick Camira fabric, generally from the Cara, Blazer Lite, Synergy or Blazer ranges.

Wall mounted tiles are supplied with self adhesive PS51/PS52 Ultramate Industrial Strength Velcro.

Ceiling hung tiles are supplied with 4 x hanging wire kits consisting of 1.5mm diameter steel cables and 2 x satin chrome ceiling and panel brackets.

On average each tile is manufactured from materials with 31% recycled content.

On average each tile is manufactured from materials with 71% recyclable content.

Screens are packaged with a single polythene bag.

SUPPLIED WITH:

Wall mounted tiles are supplied with self adhesive PS51/PS52 Ultramate Industrial Strength Velcro.

Ceiling hung tiles are supplied with 4 x hanging wire kits consisting of 1.5mm diameter steel cables and 2 x satin chrome ceiling and panel brackets.

CERTIFICATIONS:

Typical Camira fabrics used are Cara, Blazer Lite, Synergy or Blazer which have flammability performance as follows, Cara: EN 1021-1 (cigarette), BS 476 Part 7 Class 1 (Adhered), EN 13501-1 Adhered Class B, s2, d0. Blazer Lite: BS 476 Part 7 Class 1 (Adhered), BS 476 Part 6 Class 0 (Adhered), EN 13501-1 Adhered Class C, s1, d0. Synergy: EN 1021 - 1 (cigarette), EN 1021 - 2 (match), BS 7176 Low Hazard, NF D 60-013, ÖNORM B 3825 & A 3800-1, (58 kg/m3 CMHR Foam), UNI 9175 Classe 1 IM, EN 13501-1 Adhered Class D, s1, d0, EN 13501-1 Un-adhered Class E, s2, d0. Blazer: same as Synergy plus BS 476 Part 7 Class 1 (Adhered).

Conforms to BSEN 1023 part 1.

Tested by the Furniture Industry Research Association (FIRA) and certified to BSEN 1023 parts 2 & 3 - report reference TRELF32922.

Unit 1 Era Park Upper Clatford Hampshire SP11 7LW First Floor 10 Great Sutton Street London EC1V 0BX t: +44 (0) 1264 341400 f: +44 (0) 1264 341444 e: sales@erascreens.com w: www. erascreens.com Company reg no: 04195401 Vat no: 780 7693 87

