Product Specification/Data Sheet



PRODUCT DETAILS:	
Product Name:	Dainty
Product Type:	Booth
Product Shape:	Straight
Product Code:	DAX/XXXX



SPECIFICATION: Consists of a 28mm thick fabric screen. Screen height available between 800mm and 1800mm. Screen width available between 800mm and 1900mm. Internal panel construction is from 2 x 12mm medium density fibreboard (MDF), which are adhered together with 21mm brads with 70mm radius top and bottom corners on rear panels and 250mm radius top and bottom front corners on return panels. Internal panel upholitered (using water based adhesive) in timm thick Comina fabric, generally from the Cara, Lucia, Blazer Lite, Synergy or Blazer ranges. Each panel is supplied with 2 x height adjusting feet which provide 35mm of adjustment to allow for uneven floors. Desk tops are typically manufactured from 25mm thick melamine foced displacard P2 grade standard colour white Egger W980ST2 and edged to match. Desk mounting brackets are supplied as required and manufactured from mild steel powder coated in RAL 9018 white gloss polyester. 12mm MDF is Forest Stewardship Council® (FSC®) mix certified (FSC-C200033). On everage each screen is manufactured from materials with 9% recycloble content. On everage each screen is manufactured from materials with 9% recycloble content. Screens are pockaged with a single polythene bag.

SUPPLIED WITH:

Each panel is supplied with 2 x height adjusting feet which provide 35mm of adjustment to allow for uneven floors.

CERTIFICATIONS:

Typical Camira fabrics used are Cara, Lucia, Blazer Lite, Synergy or Blazer which have flammability performance as follows, Cara: EN 1021-1 (cigarette), BS 476 Part 7 Class 1 (Adhered), EN 13501-1 Adhered Class B, s2, d0. Lucia: same as Cara plus EN 1021 - 2 (match), BS 7176 Low Hazard, EN 13501-1 Un-adhered class B, s1,d2. Blazer Lite: BS 476 Part 7 Class 1 (Adhered), BS 476 Part 6 Class 0 (Adhered), EN 13501-1 Adhered Class C, s1, d0. Synergy: EN 1021 - 1 (cigarette), EN 1021 - 2 (match), BS 7176 Low Hazard, NF D 60-013, ÖNORM B 3825 & A 3800-1, (58 kg/m3 CMHR Foam), UNI 9175 Classe 1 IM, EN 13501-1 Adhered Class D, s1, d0, EN 13501-1 Un-adhered Class E, s2, d0. Blazer: same as Synergy plus BS 476 Part 7 Class 1 (Adhered).

Conforms to BSEN 1023 part 1.

Tested by the Furniture Industry Research Association (FIRA) and certified to BSEN 1023 parts 2 & 3 - report reference TRELF32922.

Unit 1 Era Park Upper Clatford Hampshire SP11 7LW First Floor 10 Great Sutton Street London EC1V 0BX

t: +44 (0) 1264 341400 f: +44 (0) 1264 341444 e: sales@erascreens.com w: www. erascreens.com Company reg no: 04195401 Vat no: 780 7693 87

