

Product Specification/Data Sheet

PRODUCT DETAILS:

| | |
|----------------|------------------------------|
| Product Name: | Ronday |
| Product Type: | Booth |
| Product Shape: | Straight, Angled or Triangle |
| Product Code: | RON/x/xP |
| | |
| | |

PRODUCT IMAGE:



SPECIFICATION:

| |
|---|
| Consists of a 25mm melamine faced chipboard (MFC) or Plywood structure. |
| Pod height is 1200mm to 1400mm. |
| Pod depth available between 850mm and 1950mm. |
| Pod width is available between 1100mm and 2000mm. |
| Outer structure, desk tops or shelving are typically manufactured from 25mm thick melamine faced chipboard (MFC) P2 grade standard colour white Egger W980ST2 and edged to match. |
| Desk mounting brackets are supplied as required and manufactured from mild steel powder coated in RAL 9016 white gloss polyester. |
| Cladded tile construction is from 6mm & 2.5mm medium density fibreboard (MDF) adhered (using water based adhesive) to 50mm sound absorbing foam. |
| Sound absorbing foam is tested to BSEN ISO 354 and has a noise reduction co-efficient (NRC) 0.90 for 50mm thick. Technical report ref no: C/23213/T01. |
| Cladded tile is upholstered (using water based adhesive) in 1mm thick Camira fabric, generally from the Cara, Blazer Lite, Synergy or Blazer ranges. |
| Cladded tiles are supplied with self adhesive PS51/PS52 Ultramate Industrial Strength Velcro. |
| Seat constructed from various timbers, foam and strapping (50mm 60% and 5% stretch webbing) all of which is mechanically fixed and adhered together (using water based adhesive). |
| Construction includes 6mm general foam and 40 and 70mm seating foam. |
| Construction includes 2.5, 9 and 18mm medium density fibreboard (MDF). |
| Construction includes 22mm square and 44mm square planed square edge (PSE) 5th grade European Redwood (pine). |
| Construction includes 2.7 thick unlined cardboard. |
| Seat base is covered in 1mm thick black cotton lining cloth. |
| Seat is upholstered (with multiple double top stitches) in 1mm thick Camira fabric, generally from the Synergy or Blazer ranges. |
| Seats are supplied with seat glides. |
| 2.5mm, 6mm, 9mm and 18mm MDF & 44mm PSE is Forest Stewardship Council® (FSC®) certified (FSC-C200033). |
| On average each pod is manufactured from materials with 37% recycled content. |
| On average each pod is manufactured from materials with 91% recyclable content. |
| Seats, tiles and panels are packaged with a single polythene bag. |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

SUPPLIED WITH:

| |
|--|
| |
| |
| |
| |
| |

CERTIFICATIONS:

| |
|---|
| Typical Camira fabrics used are Synergy or Blazer which have flammability performance as follows, Synergy: EN 1021 - 1 (cigarette), EN 1021 - 2 (match), BS 7176 Low Hazard, NF D 60-013, ÖNORM B 3825 & A 3800-1, (58 kg/m3 CMHR Foam), UNI 9175 Classe 1 IM, EN 13501-1 Adhered Class D, s1, d0, EN 13501-1 Un-adhered Class E, s2, d0. Blazer: same as Synergy plus BS 476 Part 7 Class 1 (Adhered). |
| Conforms to BSEN 1023 part 1. |
| Tested by the Furniture Industry Research Association (FIRA) and certified to BSEN 1023 parts 2 & 3 - report reference TREL32922. |

Unit 1 Era Park
Upper Clatford
Hampshire
SP11 7LW

First Floor
10 Great Sutton Street
London
EC1V 0BX

t: +44 (0) 1264 341400
f: +44 (0) 1264 341444
e: sales@erascreens.com
w: www.erascreens.com

Company reg no: 04195401
Vat no: 780 7693 87

